

# Coaxial Spot Light

## SLD-A30-□

Spot LED is a powerful LED and used for lens magnification higher than 3X. The outer dimension is designed for a maximum of 22mm to facilitate the needs of system integrators. This illuminator is useful not only for coaxial illumination but for spot illumination as well.

### Specifications

| Model                                 | SLD-A30-W               | SLD-A30-R  | SLD-A30-G  | SLD-A30-B  |
|---------------------------------------|-------------------------|------------|------------|------------|
| Input Current                         | 350mA                   |            |            |            |
| Color Temperature/<br>Peak Wavelength | 4900K typ.              | 635nm typ. | 525nm typ. | 465nm typ. |
| Cable Length                          | 500m                    |            |            |            |
| Input Connector                       | SM connector(SMR-03V-B) |            |            |            |
| Polarity                              | 1:+ 2:-                 |            |            |            |
| Ambient Temperature                   | 0~+40 C°                |            |            |            |
| Ambient Humidity                      | 35~85% (non condensing) |            |            |            |
| Weight                                | 40g                     |            |            |            |
| Adaptable Compliance                  | RoHS,IEC 62471          |            |            |            |
| Input Voltage                         | DC12V                   |            |            |            |
| Power Consumption                     | 2.0W                    |            |            |            |

### Diagram:

